

# *Bayesian Compressive Sensing Framework for Sparse Representations of High-Dimensional Models*

*K. Sargsyan<sup>1</sup>, C. Safta<sup>1</sup>, B. Debusschere<sup>1</sup>, H. Najm<sup>1</sup>  
D. Ricciuto<sup>2</sup>, P. Thornton<sup>2</sup>*

<sup>1</sup>Sandia National Laboratories  
Livermore, CA

<sup>2</sup>Oak Ridge National Laboratory  
Oak Ridge, TN

*Sponsored by DOE, Biological and Environmental Research,  
under Climate Science for Sustainable Energy Future (CSSEF).*

*Sandia National Laboratories is a multi-program laboratory operated by Sandia Corporation, a wholly owned subsidiary of Lockheed Martin Corporation, for the U.S. Department of Energy's National Nuclear Security Administration under contract DE-AC04-94AL85000.*

# OUTLINE

- Surrogates needed for complex models
- Polynomial Chaos (PC) surrogates do well with uncertain inputs
- Bayesian regression provide results with uncertainty certificate
- Compressive sensing ideas deal with high-dimensionality

# Surrogate construction: scope and challenges

Construct surrogate for a complex model  $f(\lambda)$  to enable

- Global sensitivity analysis
  - Optimization
  - Forward uncertainty propagation
  - Input parameter calibration
  - ...
- 
- Computationally expensive model simulations, data sparsity
    - Need to build accurate surrogates with as few training runs as possible
  - High-dimensional input space
    - Too many samples needed to cover the space
    - Too many terms in the polynomial expansion

# Surrogate construction: scope and challenges

Construct surrogate for a complex model  $f(\lambda)$  to enable

- Global sensitivity analysis
  - Optimization
  - Forward uncertainty propagation
  - Input parameter calibration
  - ...
- 
- Computationally expensive model simulations, data sparsity
    - Need to build accurate surrogates with as few training runs as possible
  - High-dimensional input space
    - Too many samples needed to cover the space
    - Too many terms in the polynomial expansion

# Surrogate construction: scope and challenges

Construct surrogate for a complex model  $f(\lambda)$  to enable

- Global sensitivity analysis
- Optimization
- Forward uncertainty propagation
- Input parameter calibration
- ...
  
- Computationally expensive model simulations, data sparsity
  - Need to build accurate surrogates with as few training runs as possible
- High-dimensional input space
  - Too many samples needed to cover the space
  - Too many terms in the polynomial expansion

# Polynomial Chaos surrogate

- Scale the input parameters  $\lambda_i \in [a_i, b_i]$

$$\lambda_i = \frac{a_i + b_i}{2} + \frac{b_i - a_i}{2} x_i$$

- Forward function  $f(\cdot)$ , output  $u$

$$u = f(\boldsymbol{\lambda}(\mathbf{x})) \quad \approx \quad \sum_{k=0}^{K-1} c_k \Psi_k(\mathbf{x}) \equiv g(\mathbf{x})$$

- Global sensitivity information for free
  - Sobol indices, variance-based decomposition.

# Polynomial Chaos surrogate

- Scale the input parameters  $\lambda_i \in [a_i, b_i]$

$$\lambda_i = \frac{a_i + b_i}{2} + \frac{b_i - a_i}{2} x_i$$

- Forward function  $f(\cdot)$ , output  $u$

$$u = f(\boldsymbol{\lambda}(\mathbf{x})) \quad \approx \quad \sum_{k=0}^{K-1} c_k \Psi_k(\mathbf{x}) \equiv g(\mathbf{x})$$

- Global sensitivity information for free
  - Sobol indices, variance-based decomposition.

# Polynomial Chaos surrogate

- Scale the input parameters  $\lambda_i \in [a_i, b_i]$

$$\lambda_i = \frac{a_i + b_i}{2} + \frac{b_i - a_i}{2} x_i$$

- Forward function  $f(\cdot)$ , output  $u$

$$u = f(\boldsymbol{\lambda}(\mathbf{x})) \approx \sum_{k=0}^{K-1} c_k \Psi_k(\mathbf{x}) \equiv g(\mathbf{x})$$

- Global sensitivity information for free
  - Sobol indices, variance-based decomposition.

# Alternative methods to obtain PC coefficients

$$u \simeq \sum_{k=0}^{K-1} c_k \Psi_k(\mathbf{x})$$


- Projection

$$c_k = \frac{\langle u(\mathbf{x}) \Psi_k(\mathbf{x}) \rangle}{\langle \Psi_k^2(\mathbf{x}) \rangle}$$

The integral  $\langle u(\mathbf{x}) \Psi_k(\mathbf{x}) \rangle = \int u(\mathbf{x}) \Psi_k(\mathbf{x}) d\mathbf{x}$  can be estimated by

- Monte-Carlo


$$\frac{1}{N} \sum_{j=1}^N u(\mathbf{x}_j) \Psi_k(\mathbf{x}_j)$$



many(!) random samples

- Quadrature

$$\sum_{j=1}^Q u(\mathbf{x}_j) \Psi_k(\mathbf{x}_j) w_j$$



samples at quadrature

# Alternative methods to obtain PC coefficients

$$u \simeq \sum_{k=0}^{K-1} c_k \Psi_k(\mathbf{x})$$


- Projection

$$c_k = \frac{\langle u(\mathbf{x}) \Psi_k(\mathbf{x}) \rangle}{\langle \Psi_k^2(\mathbf{x}) \rangle}$$

The integral  $\langle u(\mathbf{x}) \Psi_k(\mathbf{x}) \rangle = \int u(\mathbf{x}) \Psi_k(\mathbf{x}) d\mathbf{x}$  can be estimated by

- Monte-Carlo


$$\frac{1}{N} \sum_{j=1}^N u(\mathbf{x}_j) \Psi_k(\mathbf{x}_j)$$



many(!) random samples

- Quadrature

$$\sum_{j=1}^Q u(\mathbf{x}_j) \Psi_k(\mathbf{x}_j) w_j$$



samples at quadrature

- Bayesian regression

$$P(c_k | u(\mathbf{x}_j)) \propto P(u(\mathbf{x}_j) | c_k) P(c_k)$$



any (number of) samples

# Alternative methods to obtain PC coefficients

$$u \simeq \sum_{k=0}^{K-1} c_k \Psi_k(\mathbf{x})$$


- Projection

$$c_k = \frac{\langle u(\mathbf{x}) \Psi_k(\mathbf{x}) \rangle}{\langle \Psi_k^2(\mathbf{x}) \rangle}$$

The integral  $\langle u(\mathbf{x}) \Psi_k(\mathbf{x}) \rangle = \int u(\mathbf{x}) \Psi_k(\mathbf{x}) d\mathbf{x}$  can be estimated by

- Monte-Carlo


$$\frac{1}{N} \sum_{j=1}^N u(\mathbf{x}_j) \Psi_k(\mathbf{x}_j)$$



many(!) random samples

- Quadrature

$$\sum_{j=1}^Q u(\mathbf{x}_j) \Psi_k(\mathbf{x}_j) w_j$$



samples at quadrature

- Bayesian regression

$$\underbrace{P(\mathbf{c}|\mathcal{D})}_{\text{Posterior}} \propto \underbrace{P(\mathcal{D}|\mathbf{c})}_{\text{Likelihood}} \underbrace{P(\mathbf{c})}_{\text{Prior}}$$




any (number of) samples

# Bayesian inference of PC surrogate: high-d, low-data regime

$$y = u(\mathbf{x}) \approx \sum_{k=0}^{K-1} c_k \Psi_k(\mathbf{x})$$

$$\Psi_k(x_1, x_2, \dots, x_d) = \psi_{k1}(x_1)\psi_{k2}(x_2) \cdots \psi_{kd}(x_d)$$




- Issues:
  - how to properly choose the basis set?
  - need to work in underdetermined regime  $N < K$ : fewer data than bases (d.o.f.)
- Discover the underlying low-d structure in the model
  - get help from the machine learning community

# Bayesian inference of PC surrogate: high-d, low-data regime

$$y = u(\mathbf{x}) \approx \sum_{k=0}^{K-1} c_k \Psi_k(\mathbf{x})$$

$$\Psi_k(x_1, x_2, \dots, x_d) = \psi_{k1}(x_1)\psi_{k2}(x_2) \cdots \psi_{kd}(x_d)$$




- Issues:
  - how to properly choose the basis set?
  - need to work in underdetermined regime  
 $N < K$ : fewer data than bases (d.o.f.)
- Discover the underlying low-d structure in the model
  - get help from the machine learning community

# Bayesian inference of PC surrogate: high-d, low-data regime

$$y = u(\mathbf{x}) \approx \sum_{k=0}^{K-1} c_k \Psi_k(\mathbf{x})$$

$$\Psi_k(x_1, x_2, \dots, x_d) = \psi_{k1}(x_1)\psi_{k2}(x_2) \cdots \psi_{kd}(x_d)$$




- Issues:
  - how to properly choose the basis set?
  - need to work in underdetermined regime  
 $N < K$ : fewer data than bases (d.o.f.)
- Discover the underlying low-d structure in the model
  - get help from the machine learning community

# Bayesian inference of PC surrogate: high-d, low-data regime

$$y = u(\mathbf{x}) \approx \sum_{k=0}^{K-1} c_k \Psi_k(\mathbf{x})$$

$$\Psi_k(x_1, x_2, \dots, x_d) = \psi_{k1}(x_1)\psi_{k2}(x_2) \cdots \psi_{kd}(x_d)$$




- Issues:
  - how to properly choose the basis set?
  - need to work in underdetermined regime  $N < K$ : fewer data than bases (d.o.f.)
- Discover the underlying low-d structure in the model
  - get help from the machine learning community

# Bayesian inference of PC surrogate: high-d, low-data regime

$$y = u(\mathbf{x}) \approx \sum_{k=0}^{K-1} c_k \Psi_k(\mathbf{x})$$

$$\Psi_k(x_1, x_2, \dots, x_d) = \psi_{k1}(x_1)\psi_{k2}(x_2) \cdots \psi_{kd}(x_d)$$

- Issues:
  - how to properly choose the basis set?
  - need to work in underdetermined regime  
 $N < K$ : fewer data than bases (d.o.f.)
- Discover the underlying low-d structure in the model
  - get help from the machine learning community



# In a different language....

- $N$  training data points  $(\mathbf{x}_n, u_n)$  and  $K$  basis terms  $\Psi_k(\cdot)$
- Projection matrix  $\mathbf{P}^{N \times K}$  with  $\mathbf{P}_{nk} = \Psi_k(\mathbf{x}_n)$
- Find regression weights  $\mathbf{c} = (c_0, \dots, c_{K-1})$  so that

$$\mathbf{u} \approx \mathbf{P}\mathbf{c}$$

or

$$u_n \approx \sum_k c_k \Psi_k(\mathbf{x}_n)$$

- The number of polynomial basis terms grows fast; a  $p$ -th order,  $d$ -dimensional basis has a total of  $K = (p+d)!/(p!d!)$  terms.
- For limited data and large basis set ( $N < K$ ) this is a sparse signal recovery problem  $\Rightarrow$  need some regularization/constraints.
- Least-squares  $\operatorname{argmin}_{\mathbf{c}} \{\|\mathbf{u} - \mathbf{P}\mathbf{c}\|_2\}$
- The ‘sparsest’  $\operatorname{argmin}_{\mathbf{c}} \{\|\mathbf{u} - \mathbf{P}\mathbf{c}\|_2 + \alpha \|\mathbf{c}\|_0\}$
- Compressive sensing  $\operatorname{argmin}_{\mathbf{c}} \{\|\mathbf{u} - \mathbf{P}\mathbf{c}\|_2 + \alpha \|\mathbf{c}\|_1\}$

# In a different language....

- $N$  training data points  $(\mathbf{x}_n, u_n)$  and  $K$  basis terms  $\Psi_k(\cdot)$
- Projection matrix  $\mathbf{P}^{N \times K}$  with  $P_{nk} = \Psi_k(\mathbf{x}_n)$
- Find regression weights  $\mathbf{c} = (c_0, \dots, c_{K-1})$  so that

$$\mathbf{u} \approx \mathbf{P}\mathbf{c}$$

or

$$u_n \approx \sum_k c_k \Psi_k(\mathbf{x}_n)$$

- The number of polynomial basis terms grows fast; a  $p$ -th order,  $d$ -dimensional basis has a total of  $K = (p+d)!/(p!d!)$  terms.
- For limited data and large basis set ( $N < K$ ) this is a sparse signal recovery problem  $\Rightarrow$  need some regularization/constraints.
- Least-squares  $\operatorname{argmin}_{\mathbf{c}} \{\|\mathbf{u} - \mathbf{P}\mathbf{c}\|_2\}$
- The ‘sparsest’  $\operatorname{argmin}_{\mathbf{c}} \{\|\mathbf{u} - \mathbf{P}\mathbf{c}\|_2 + \alpha \|\mathbf{c}\|_0\}$
- Compressive sensing  
Bayesian  $\operatorname{argmin}_{\mathbf{c}} \{\|\mathbf{u} - \mathbf{P}\mathbf{c}\|_2 + \alpha \|\mathbf{c}\|_1\}$   
Likelihood Prior

# Bayesian Compressive Sensing (BCS), or Relevance Vector Machine (RVM)

- Dimensionality reduction by using hierarchical priors

$$p(c_k | \sigma_k^2) = \frac{1}{\sqrt{2\pi}\sigma_k} e^{-\frac{c_k^2}{2\sigma_k^2}}$$
$$p(\sigma_k^2 | \alpha) = \frac{\alpha}{2} e^{-\frac{\alpha\sigma_k^2}{2}}$$

- Effectively, one obtains Laplace sparsity prior

$$p(\mathbf{c} | \alpha) = \int \prod_{k=0}^{K-1} p(c_k | \sigma_k^2) p(\sigma_k^2 | \alpha) d\sigma_k^2 = \prod_{k=0}^{K-1} \frac{\sqrt{\alpha}}{2} e^{-\sqrt{\alpha}|c_k|}$$

- The parameter  $\alpha$  can be further modeled hierarchically, or fixed.
- Evidence maximization dictates values for  $\sigma_k^2, \alpha, \sigma^2$  and allows exact Bayesian solution

$$\mathbf{c} \sim \mathcal{MVN}(\boldsymbol{\mu}, \boldsymbol{\Sigma})$$

with

$$\boldsymbol{\mu} = \sigma^{-2} \boldsymbol{\Sigma} \mathbf{P}^T \mathbf{u}$$
$$\boldsymbol{\Sigma} = \sigma^2 (\mathbf{P}^T \mathbf{P} + \text{diag}(\sigma^2 / \sigma_k^2))^{-1}$$

[Tipping, 2001, Ji et al., 2008; Babacan et al., 2010]

# Bayesian Compressive Sensing (BCS), or Relevance Vector Machine (RVM)

- Dimensionality reduction by using hierarchical priors

$$p(c_k | \sigma_k^2) = \frac{1}{\sqrt{2\pi}\sigma_k} e^{-\frac{c_k^2}{2\sigma_k^2}}$$
$$p(\sigma_k^2 | \alpha) = \frac{\alpha}{2} e^{-\frac{\alpha\sigma_k^2}{2}}$$

- Effectively, one obtains Laplace *sparsity* prior

$$p(\mathbf{c} | \alpha) = \int \prod_{k=0}^{K-1} p(c_k | \sigma_k^2) p(\sigma_k^2 | \alpha) d\sigma_k^2 = \prod_{k=0}^{K-1} \frac{\sqrt{\alpha}}{2} e^{-\sqrt{\alpha}|c_k|}$$

- The parameter  $\alpha$  can be further modeled hierarchically, or fixed.
- Evidence maximization dictates values for  $\sigma_k^2, \alpha, \sigma^2$  and allows exact Bayesian solution

$$\mathbf{c} \sim \mathcal{MVN}(\boldsymbol{\mu}, \boldsymbol{\Sigma})$$

with

$$\boldsymbol{\mu} = \sigma^{-2} \boldsymbol{\Sigma} \mathbf{P}^T \mathbf{u}$$
$$\boldsymbol{\Sigma} = \sigma^2 (\mathbf{P}^T \mathbf{P} + \text{diag}(\sigma^2 / \sigma_k^2))^{-1}$$

[Tipping, 2001, Ji et al., 2008; Babacan et al., 2010]

# Bayesian Compressive Sensing (BCS), or Relevance Vector Machine (RVM)

- Dimensionality reduction by using hierarchical priors

$$p(c_k | \sigma_k^2) = \frac{1}{\sqrt{2\pi}\sigma_k} e^{-\frac{c_k^2}{2\sigma_k^2}} \quad p(\sigma_k^2 | \alpha) = \frac{\alpha}{2} e^{-\frac{\alpha\sigma_k^2}{2}}$$

- Effectively, one obtains Laplace *sparsity* prior

$$p(\mathbf{c} | \alpha) = \int \prod_{k=0}^{K-1} p(c_k | \sigma_k^2) p(\sigma_k^2 | \alpha) d\sigma_k^2 = \prod_{k=0}^{K-1} \frac{\sqrt{\alpha}}{2} e^{-\sqrt{\alpha}|c_k|}$$

- The parameter  $\alpha$  can be further modeled hierarchically, or fixed.
- Evidence maximization dictates values for  $\sigma_k^2, \alpha, \sigma^2$  and allows exact Bayesian solution

$$\mathbf{c} \sim \mathcal{MVN}(\boldsymbol{\mu}, \boldsymbol{\Sigma})$$

with

$$\boldsymbol{\mu} = \sigma^{-2} \boldsymbol{\Sigma} \mathbf{P}^T \mathbf{u} \quad \boldsymbol{\Sigma} = \sigma^2 (\mathbf{P}^T \mathbf{P} + \text{diag}(\sigma^2 / \sigma_k^2))^{-1}$$

[Tipping, 2001, Ji et al., 2008; Babacan et al., 2010]

# Bayesian Compressive Sensing (BCS), or Relevance Vector Machine (RVM)

- Dimensionality reduction by using hierarchical priors

$$p(c_k | \sigma_k^2) = \frac{1}{\sqrt{2\pi}\sigma_k} e^{-\frac{c_k^2}{2\sigma_k^2}}$$
$$p(\sigma_k^2 | \alpha) = \frac{\alpha}{2} e^{-\frac{\alpha\sigma_k^2}{2}}$$

- Effectively, one obtains Laplace *sparsity* prior

$$p(\mathbf{c} | \alpha) = \int \prod_{k=0}^{K-1} p(c_k | \sigma_k^2) p(\sigma_k^2 | \alpha) d\sigma_k^2 = \prod_{k=0}^{K-1} \frac{\sqrt{\alpha}}{2} e^{-\sqrt{\alpha}|c_k|}$$

- The parameter  $\alpha$  can be further modeled hierarchically, or fixed.
- Evidence maximization dictates values for  $\sigma_k^2, \alpha, \sigma^2$  and allows exact Bayesian solution

$$\mathbf{c} \sim \mathcal{MVN}(\boldsymbol{\mu}, \boldsymbol{\Sigma})$$

with


$$\boldsymbol{\mu} = \sigma^{-2} \boldsymbol{\Sigma} \mathbf{P}^T \mathbf{u}$$
$$\boldsymbol{\Sigma} = \sigma^2 (\mathbf{P}^T \mathbf{P} + \text{diag}(\sigma^2 / \sigma_k^2))^{-1}$$

- KEY: Some  $\sigma_k^2 \rightarrow 0$ , hence the corresponding basis terms are dropped.

[Tipping, 2001; Ji et al., 2008; Babacan et al., 2010]

# BCS removes unnecessary basis terms

$$f(x, y) = \cos(x + 4y)$$



$$f(x, y) = \cos(x^2 + 4y)$$




## Success rate grows with more data and ‘sparser’ model

Consider test function

$$f(\mathbf{x}) = \sum_{k=0}^{K-1} c_k \Psi_k(\mathbf{x})$$

where only  $S$  coefficients  $c_k$  are non-zero. Typical setting is

$$S < N < K$$




## Success rate grows with more data and ‘sparser’ model

Consider test function


$$f(\mathbf{x}) = \sum_{k=0}^{K-1} c_k \Psi_k(\mathbf{x})$$

where only  $S$  coefficients  $c_k$  are non-zero. Typical setting is


$$S < N < K$$




# BCS recovers true PC coefficients with increased number of measurements



# BCS recovers true PC coefficients with increased number of measurements



# BCS recovers true PC coefficients with increased number of measurements



# Bayesian Compressive Sensing

- Dimensionality reduction by using hierarchical priors

$$p(c_k|\sigma_k^2) = \frac{1}{\sqrt{2\pi}\sigma_k} e^{-\frac{c_k^2}{2\sigma_k^2}}$$
$$p(\sigma_k^2|\alpha) = \frac{\alpha}{2} e^{-\frac{\alpha\sigma_k^2}{2}}$$

- Effectively, one obtains Laplace *sparsity* prior

$$p(\mathbf{c}|\boldsymbol{\alpha}) = \int \prod_{k=0}^{K-1} p(c_k|\sigma_k^2)p(\sigma_k^2|\alpha) d\sigma_k^2 = \prod_{k=0}^{K-1} \frac{\sqrt{\alpha}}{2} e^{-\sqrt{\alpha}|c_k|}$$

- The parameter  $\alpha$  can be further modeled hierarchically, or fixed.
- Evidence maximization dictates values for  $\sigma_k^2, \alpha, \sigma^2$  and allows exact Bayesian solution

$$\mathbf{c} \sim \mathcal{MVN}(\boldsymbol{\mu}, \boldsymbol{\Sigma})$$

with

$$\boldsymbol{\mu} = \sigma^{-2} \boldsymbol{\Sigma} \mathbf{P}^T \mathbf{u}$$
$$\boldsymbol{\Sigma} = \sigma^2 (\mathbf{P}^T \mathbf{P} + \text{diag}(\sigma^2/\sigma_k^2))^{-1}$$

- KEY: Some  $\sigma_k^2 \rightarrow 0$ , hence the corresponding basis terms are dropped.

# Weighted Bayesian Compressive Sensing

- Dimensionality reduction by using hierarchical priors

$$p(c_k|\sigma_k^2) = \frac{1}{\sqrt{2\pi}\sigma_k} e^{-\frac{c_k^2}{2\sigma_k^2}}$$
$$p(\sigma_k^2|\alpha_{\textcolor{red}{k}}) = \frac{\alpha_{\textcolor{red}{k}}}{2} e^{-\frac{\alpha_{\textcolor{red}{k}}\sigma_k^2}{2}}$$

- Effectively, one obtains Laplace *sparsity* prior

$$p(\mathbf{c}|\boldsymbol{\alpha}) = \int \prod_{k=0}^{K-1} p(c_k|\sigma_k^2)p(\sigma_k^2|\alpha_{\textcolor{red}{k}})d\sigma_k^2 = \prod_{k=0}^{K-1} \frac{\sqrt{\alpha_{\textcolor{red}{k}}}}{2} e^{-\sqrt{\alpha_{\textcolor{red}{k}}} |c_k|}$$

- The parameter  $\alpha_{\textcolor{red}{k}}$  can be further modeled hierarchically, or fixed.
- Evidence maximization dictates values for  $\sigma_k^2, \alpha_{\textcolor{red}{k}}, \sigma^2$  and allows exact Bayesian solution


$$\mathbf{c} \sim \mathcal{MVN}(\boldsymbol{\mu}, \boldsymbol{\Sigma})$$

with

$$\boldsymbol{\mu} = \sigma^{-2} \boldsymbol{\Sigma} \mathbf{P}^T \mathbf{u}$$
$$\boldsymbol{\Sigma} = \sigma^2 (\mathbf{P}^T \mathbf{P} + \text{diag}(\sigma^2/\sigma_k^2))^{-1}$$

- KEY: Some  $\sigma_k^2 \rightarrow 0$ , hence the corresponding basis terms are dropped.

# WBCS recovers true coefficients better



$$f(\mathbf{x}) = x_0 \cos \left( e + \sum_{i=1}^9 x_i / i \right)$$

Sparsest solution:  $\min\|c\|_0$  such that  $u \approx P c$

Compressive sensing:  $\min\|c\|_1$  such that  $u \approx P c$

Weighted compressive sensing:  $\min\|Wc\|_1$  such that  $u \approx P c$

Sparsest solution:  $\min\|\mathbf{c}\|_0$  such that  $\mathbf{u} \approx \mathbf{P}\mathbf{c}$

Compressive sensing:  $\min\|\mathbf{c}\|_1$  such that  $\mathbf{u} \approx \mathbf{P}\mathbf{c}$

Weighted compressive sensing:  $\min\|\mathbf{W}\mathbf{c}\|_1$  such that  $\mathbf{u} \approx \mathbf{P}\mathbf{c}$

For sparse signals,  $\mathbf{u} = \mathbf{P}\mathbf{c}^s$ , with  $\|\mathbf{c}_s\|_0 = S < K$ , ideal weights are

$$\mathbf{W} = \text{diag} \left( \frac{1}{|c_k^s|} \right) \quad [\text{i.e., } W_{kk} = +\infty \text{ if } c_k^s = 0]$$

In practice, the true signal coefficients are not known, so...

Sparsest solution:  $\min \|\mathbf{c}\|_0$  such that  $\mathbf{u} \approx \mathbf{P}\mathbf{c}$

Compressive sensing:  $\min \|\mathbf{c}\|_1$  such that  $\mathbf{u} \approx \mathbf{P}\mathbf{c}$

Weighted compressive sensing:  $\min \|\mathbf{W}\mathbf{c}\|_1$  such that  $\mathbf{u} \approx \mathbf{P}\mathbf{c}$

For sparse signals,  $\mathbf{u} = \mathbf{P}\mathbf{c}^s$ , with  $\|\mathbf{c}_s\|_0 = S < K$ , ideal weights are

$$\mathbf{W} = \text{diag} \left( \frac{1}{|c_k^s|} \right) \quad [\text{i.e., } W_{kk} = +\infty \text{ if } c_k^s = 0]$$


In practice, the true signal coefficients are not known, so...

Iterative re-weighting

$$\mathbf{W}^{(i+1)} = \text{diag} \left( \frac{1}{|c_k^{(i)}| + \epsilon} \right) \quad [\epsilon \ll 1 \text{ for stability}]$$


# Iterative Bayesian Compressive Sensing (iBCS)

- *Iterative BCS*: We implement an iterative procedure that allows increasing the order for the relevant basis terms while maintaining the dimensionality reduction [Sargsyan *et al.* 2014].




# Iterative Bayesian Compressive Sensing (iBCS)

- Combine basis growth and reweighting!




# Basis set growth

$$f(x, y) = \cos(x + 4y)$$



# Application of Interest: Community Land Model





<http://www.cesm.ucar.edu/models/clm/>

- Nested computational grid hierarchy
- A single-site, 1000-yr simulation takes  $\sim 10$  hrs on 1 CPU
- Involves  $\sim 70$  input parameters; some dependent
- Non-smooth input-output relationship



# Sparse PC surrogate for the Community Land Model

- Main effect sensitivities : rank input parameters
  - Joint sensitivities : most influential input couplings
  - About 200 polynomial basis terms in the 70-dimensional space
  - Sparse PC will further be used for
    - sampling in a reduced space
    - parameter calibration against experimental data




# Sparse PC surrogate for the Community Land Model

- Main effect sensitivities : rank input parameters
- Joint sensitivities : most influential input couplings
- About 200 polynomial basis terms in the 70-dimensional space
- Sparse PC will further be used for
  - sampling in a reduced space
  - parameter calibration against experimental data



# Sparse PC surrogate for the Community Land Model

- Main effect sensitivities : rank input parameters
- Joint sensitivities : most influential input couplings
- About 200 polynomial basis terms in the 70-dimensional space
- Sparse PC will further be used for
  - sampling in a reduced space
  - parameter calibration against experimental data



# Summary

- Surrogate models are necessary for complex models
  - Replace the full model for both forward and inverse UQ
- Uncertain inputs
  - Polynomial Chaos surrogates well-suited
- Limited training dataset
  - Bayesian methods handle limited information well
- Curse of dimensionality
  - The hope is that not too many dimensions matter
  - Compressive sensing (CS) ideas ported from machine learning
  - We implemented *iteratively reweighting Bayesian CS* algorithm that reduces dimensionality and increases order on-the-fly.

---

- Future work, open issues
  - Computational design. What is the best sampling strategy?
  - Overfitting still present. Cross-validation techniques help.

# Literature

- M. Tipping, "Sparse Bayesian learning and the relevance vector machine", *J Machine Learning Research*, 1, pp. 211-244, 2001.
- S. Ji, Y. Xue and L. Carin, "Bayesian compressive sensing", *IEEE Trans. Signal Proc.*, 56:6, 2008.
- S. Babacan, R. Molina and A. Katsaggelos, "Bayesian compressive sensing using Laplace priors", *IEEE Trans. Image Proc.*, 19:1, 2010.
- E. J. Candes, M. Wakin and S. Boyd. "Enhancing sparsity by reweighted  $\ell_1$  minimization", *J. Fourier Anal. Appl.*, 14 877-905, 2007.
- A. Saltelli, "Making best use of model evaluations to compute sensitivity indices", *Comp Phys Comm*, 145, 2002.
- K. Sargsyan, C. Safta, H. Najm, B. Debusschere, D. Ricciuto and P. Thornton, "Dimensionality reduction for complex models via Bayesian compressive sensing", *Int J for Uncertainty Quantification*, 4(1), pp. 63-93, 2014.

Thank You

# Random variables represented by Polynomial Chaos

$$X \simeq \sum_{k=0}^{K-1} c_k \Psi_k(\boldsymbol{\eta})$$


- $\boldsymbol{\eta} = (\eta_1, \dots, \eta_d)$  standard i.i.d. r.v.  
 $\Psi_k$  standard polynomials, orthogonal w.r.t.  $\pi(\boldsymbol{\eta})$ .

$$\Psi_k(\eta_1, \eta_2, \dots, \eta_d) = \psi_{k_1}(\eta_1)\psi_{k_2}(\eta_2)\cdots\psi_{k_d}(\eta_d)$$

- Typical truncation rule: total-order  $p$ ,  $k_1 + k_2 + \dots + k_d \leq p$ .  
Number of terms is  $K = \frac{(d+p)!}{d!p!}$ .
- Essentially, a parameterization of a r.v. by deterministic spectral modes  $c_k$ .
- Most common standard Polynomial-Variable pairs:  
(continuous) Gauss-Hermite, Legendre-Uniform,  
(discrete) Poisson-Charlier.

[Wiener, 1938; Ghanem & Spanos, 1991; Xiu & Karniadakis, 2002; Le Maître & Knio, 2010]

# Basis normalization helps the success rate



## Input correlations: Rosenblatt transformation

- Rosenblatt transformation maps any (not necessarily independent) set of random variables  $\lambda = (\lambda_1, \dots, \lambda_d)$  to uniform i.i.d.'s  $\{\eta_i\}_{i=1}^d$  [Rosenblatt, 1952].


$$\eta_1 = F_1(\lambda_1)$$

$$\eta_2 = F_{2|1}(\lambda_2|\lambda_1)$$

$$\eta_3 = F_{3|2,1}(\lambda_3|\lambda_2, \lambda_1)$$

⋮

$$\eta_d = F_{d|d-1, \dots, 1}(\lambda_d|\lambda_{d-1}, \dots, \lambda_1)$$



- Inverse Rosenblatt transformation  $\lambda = R^{-1}(\eta)$  ensures a well-defined input PC construction

$$\lambda_i = \sum_{k=0}^{K-1} \lambda_{ik} \Psi_k(\eta)$$

- Caveat: the conditional distributions are often hard to evaluate accurately.

# Strong discontinuities/nonlinearities challenge global polynomial expansions

- Basis enrichment [Ghosh & Ghanem, 2005]
- Stochastic domain decomposition
  - Wiener-Haar expansions,  
Multiblock expansions,  
Multiwavelets, [Le Maître *et al*, 2004,2007]
  - also known as Multielement PC [Wan & Karniadakis, 2009]
- Smart splitting, discontinuity detection  
[Archibald *et al*, 2009; Chantrasmi, 2011; Sargsyan *et al*, 2011; Jakeman *et al*, 2012]
- Data domain decomposition,
  - Mixture PC expansions [Sargsyan *et al*, 2010]
- Data clustering, classification,
  - Piecewise PC expansions

## Piecewise PC expansion with classification

- Cluster the training dataset into non-overlapping subsets  $\mathcal{D}_1$  and  $\mathcal{D}_2$ ,  
where the behavior of function is smoother
- Construct global PC expansions  $g_i(\mathbf{x}) = \sum_k c_{ik} \Psi_k(\mathbf{x})$  using  
each dataset individually ( $i = 1, 2$ )
- Declare a surrogate



$$g_s(\mathbf{x}) = \begin{cases} g_1(\mathbf{x}) & \text{if } \mathbf{x} \in^* \mathcal{D}_1 \\ g_2(\mathbf{x}) & \text{if } \mathbf{x} \in^* \mathcal{D}_2 \end{cases}$$

\* Requires a classification step to find out which cluster  $\mathbf{x}$  belongs to. We applied Random Decision Forests (RDF).

- Caveat: the sensitivity information is harder to obtain.



# Illustration of piecewise PC construction

Global 5-th order surrogate fails





# Illustration of piecewise PC construction

## Piecewise 2-nd order surrogate





# Illustration of piecewise PC construction

Piecewise 5-th order surrogate





# Illustration of piecewise PC construction

Piecewise 5-th order surrogate




# Illustration of piecewise PC construction

Piecewise 5-th order surrogate



# Illustration of piecewise PC construction



Sensitivity information comes free with PC surrogate,

$$g(x_1, \dots, x_d) = \sum_{k=0}^{K-1} c_k \Psi_k(\mathbf{x})$$

- Main effect sensitivity indices

$$S_i = \frac{Var[\mathbb{E}(g(\mathbf{x}|x_i)]}{Var[g(\mathbf{x})]} = \frac{\sum_{k \in \mathbb{I}_i} c_k^2 ||\Psi_k||^2}{\sum_{k>0} c_k^2 ||\Psi_k||^2}$$

$\mathbb{I}_i$  is the set of bases with only  $x_i$  involved

Sensitivity information comes free with PC surrogate,

$$g(x_1, \dots, x_d) = \sum_{k=0}^{K-1} c_k \Psi_k(\mathbf{x})$$

- Main effect sensitivity indices

$$S_i = \frac{Var[\mathbb{E}(g(\mathbf{x}|x_i)]}{Var[g(\mathbf{x})]} = \frac{\sum_{k \in \mathbb{I}_i} c_k^2 ||\Psi_k||^2}{\sum_{k>0} c_k^2 ||\Psi_k||^2}$$

- Joint sensitivity indices

$$S_{ij} = \frac{Var[\mathbb{E}(g(\mathbf{x}|x_i, x_j)]}{Var[g(\mathbf{x})]} - S_i - S_j = \frac{\sum_{k \in \mathbb{I}_{ij}} c_k^2 ||\Psi_k||^2}{\sum_{k>0} c_k^2 ||\Psi_k||^2}$$

$\mathbb{I}_{ij}$  is the set of bases with only  $x_i$  and  $x_j$  involved

Sensitivity information comes free with PC surrogate,  
but not with piecewise PC

$$g(x_1, \dots, x_d) = \sum_{k=0}^{K-1} c_k \Psi_k(\mathbf{x})$$

- Main effect sensitivity indices

$$S_i = \frac{\text{Var}[\mathbb{E}(g(\mathbf{x}|x_i)]}{\text{Var}[g(\mathbf{x})]} = \frac{\sum_{k \in \mathbb{I}_i} c_k^2 \|\Psi_k\|^2}{\sum_{k>0} c_k^2 \|\Psi_k\|^2}$$

- Joint sensitivity indices

$$S_{ij} = \frac{\text{Var}[\mathbb{E}(g(\mathbf{x}|x_i, x_j)]}{\text{Var}[g(\mathbf{x})]} - S_i - S_j = \frac{\sum_{k \in \mathbb{I}_{ij}} c_k^2 \|\Psi_k\|^2}{\sum_{k>0} c_k^2 \|\Psi_k\|^2}$$

- For piecewise PC, need to resort to Monte-Carlo estimation  
[\[Saltelli, 2002\]](#).